

# GHE LIFTING SPECIALIST

ABN 50 107 218 048

Unit 17  
36 Tikalara Street  
Regency Park SA 5010

Phone: (08) 8340 9755  
Fax: (08) 8340 9766  
Email: info@gheliftingspecialist.com.au  
Web: www.gheliftingspecialist.com.au

## PACIFIC ELECTRIC WINCH

Precision engineered, heavy duty construction - available in a range of single and three phase models suitable for a range of hoisting and pulling applications.

Features:

- \* High performance with low maintenance
- \* Brakes designed for both static and dynamic loading that automatically apply in the event of power loss
- \* IP65 Pendant control
- \* 24V push button control supplied as standard on three phase models
- \* Compact load sharing design of the heat treated planetary gear ensures quiet operation and long life
- \* Lightweight and compact - CWL series electric winches are ideal for portable use



Applications:

- \* Designed hoisting applications
- \* Hauling operations
- \* Construction sites
- \* Timber yards
- \* Elevator & Rigging industry

Dimensions:

Model	A	B	C	D	E	F
CWL-200	8 x ø11	142	132	416	210	270
CWL-200L	8 x ø11	197	135	471	210	270
CP-200	4 x ø10.5	142	142	548	210	241
CP-250	4 x ø10.5	142	142	548	210	241
CP-300	4 x ø10.5	142	142	548	210	241
CP-500	4 x ø13.5	267	156	694	260	299
CP750	6 x ø16	400	300	870	347	360
CWG-10077	4 x ø13.5	137	156	630	240	300
CWG-30075	4 x ø10.5	142	142	548	210	241
CWG-10151	4 x ø16	400	325	922	367	425
CWG-30151	4 x ø16	400	325	922	367	425
CWG-30265	4 x ø16	400	325	940	367	425
CWG-30375	4 x ø16	500	370	1009	400	445
CWG-30565	4 x ø16	620	495	1120	470	520
CWG-30750	4 x ø22	600	499	1246	565	658
CWG-31500	8 x ø30	847	680	1439	740	860
CWG-34000	8 x ø32	920	680	1860	740	905

Specifications:

Model	Lift Capacity kg	Speed M/min	Phase Voltage	Wire Rope omm x m	Weight kg
CWL-200	200	16	240 x 1	6 x 30	16
CWL-200L	200	16	240 x 1	5 x 71	19
CP-200	200	10-15	240 x 1	6 x 30	32
CP-250	250	10-15	240 x 1	6 x 30	34
CP-300	300	10-15	240 x 1	6 x 30	37
CP-500	500	11.6-18.3	240 x 1	7 x 60	54
CP-750	750	10-15	415 x 3	9 x 60	135
CWG-10077	300	12-17	240 x 1	7 x 40	44
CWG-30075	300	10-15	415 x 3	6 x 30	120
CWG-10151	400	12-18	240 x 1	9 x 60	120
CWG-30151	500	12-18	415 x 3	9 x 60	120
CWG-30265	650	12-18	415 x 3	9 x 60	160
CWG-30375	900	13-20.6	415 x 3	10 x 60	220
CWG-30565	1100	14-25	415 x 3	12 x 100	290
CWG-30750	2200	7-12	415 x 3	16 x 100	450
CWG-31500	3500	6.3-8	415 x 3	18 x 120	860
CWG-34000	5000	8-11.2	415 x 3	22.4 x 150	1500

